

534,070

Rec'd PCT/PTO 06 MAY 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/048961 A1

(51) International Patent Classification⁷: G01N 27/411, 33/20

(72) Inventors; and
(75) Inventors/Applicants (*for US only*): MERKENS, Wilhelm [DE/DE]; Krickelberg 89, 41836 Hückelhoven (DE). SCHMITZ, Norbert [DE/DE]; Luisenstrasse 29, 47799 Krefeld (DE).

(21) International Application Number: PCT/EP2003/013012

(74) Agent: GROSSE BOCKHORNI SCHUMACHER; Frühlingstr. 43A, 45133 Essen (DE).

(22) International Filing Date: 20 November 2003 (20.11.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data: 102 55 282.7 26 November 2002 (26.11.2002) DE

(71) Applicant (*for all designated States except US*): SPECIALTY MINERALS MICHIGAN INC. [US/US]; 30600 Telegraph Road, Bingham Farms, MI 49025 (US).

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: PROBE FOR DETERMINATION OF OXYGEN ACTIVITY IN METAL MELTS AND METHODS FOR ITS PRODUCTION



(57) Abstract: The invention relates to a probe (100, 200, 300, 400, 500, 600) for the measurement of the oxygen activity of metal melts, in particular steel melts, comprising a reference substance (2) of known oxygen activity in electrically conducting contact (3) with a measuring device; and comprising a solid electrolyte predominantly oxygen ion conducting and negligibly electron conducting at high temperatures and separating the reference substance (2) from the metal melt and having an entry surface (4) for oxygen ions which is in contact with the metal melt, wherein the entry surface (4) of the probe ready for operation is covered by a functional foil arrangement (10,20) in close contact to the entry surface (4).

BEST AVAILABLE COPY

WO 2004/048961 A1